



# PRAMAC GSW65P COFANATO CON QUADRO COMANDO MANUALE

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 53.54

Continuous power three phase (KW): 48.58

Maximum power three phase (KVA): 66.93

Continuous power three phase (KVA): 60.73

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: PERKINS 1103A-33TG2, turbocharged

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3300

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 8.3

Cooling: Water

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 10.4 at 75% of the load / 13.9 at 100% of the load

Running time (h): 20.1 at 75% of the load / 15 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2285



Width (mm): 920  
Height (mm): 1465  
Dry weight (Kg): 1085  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Perkins