



PRAMAC GSW80P COFANATO CON QUADRO COMANDO MANUALE

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 66.4

Continuous power three phase (KW): 62.4

Maximum power three phase (KVA): 83

Continuous power three phase (KVA): 78

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: PERKINS 1104A-44TG2, turbocharged

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4400

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 8

Cooling: Water

Alternator: Mecc Alte ECO/P32-3L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 13.4 at 75% of the load / 17.9 at 100% of the load

Running time (h): 15.5 at 75% of the load / 11.7 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2285



Width (mm): 920
Height (mm): 1465
Dry weight (Kg): 1144
Silenced: Yes
Super silenced: Yes
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Perkins