



PRAMAC W 220 TDC



Product price:

2.200,00 € tax excluded

Product description:

PRAMAC W220 TDC 5.5 KW ENGINE-DRIVEN WELDER

PRAMAC W220 TDC is a lightweight and compact engine-driven welder, equipped with a Honda GX390 Recoil petrol engine capable of delivering 5.5 kW of power.

PRAMAC engine-driven welders are the ideal choice for small repairs or more demanding craft applications.

With a power of 220 A, it is possible to use rutile, basic, or cellulosic electrodes up to 5 mm in diameter.

Mechanical adjustment of the welding current.

Reliability, robustness, and quiet operation to meet every need.

TECHNICAL SPECIFICATIONS PRAMAC W220 TDC

Maximum single-phase power: 2.4 kW

Continuous single-phase power: 2 kW

Maximum three-phase power: 5.5 kW

Continuous three-phase power: 4.16 kW

Fuel: Petrol





Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Honda GX390 recoil start

Starting: Recoil start

Welding current: 40-220 A

Welding voltage min/max: 21.6 V / 28.8 V

Electrode diameter: 5 mm

Consumption: 2.2 l/h at 75% load

Length: 875 mm

Width: 620 mm

Height: 600 mm

Weight: 80 Kg

if you are looking for a product with similar features [CLICK HERE](#). You will find the entire dedicated category.

Images and technical data are not binding. Always refer to the technical data sheet issued by the manufacturer.

Manel service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.4

Continuous power single phase (KW): 2

Maximum power single phase (KVA): 2.7

Continuous power single phase (KVA): 2.3

Maximum power three phase (KW): 5.5

Continuous power three phase (KW): 4.16

Maximum power three phase (KVA): 6.1





Continuous power three phase (KVA): 5.2

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Honda GX390 Recoil, naturally aspirated

Speed governor: Mechanical

Starting system: Pull starter

Engine capacity (cm³): 389

Oil capacity (L): 1.1

Cooling: Air

Welding current (A): 40-220

Welding voltage min/max (V): 21.6 / 28.8

Diameter electrodes (mm): 5

Fuel tank capacity (L): 6.1

Consumption (L/h): 0,8 al 75% del carico

Running time (h): 2.8 at 75% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 875

Width (mm): 620

Height (mm): 600

Dry weight (Kg): 80

Silenced: No

Super silenced: No

ATS Switch device : No

Voltage regulator: No

Engine manufacturer: Honda