



# PRAMAC W220 TDC 5.5KW Motor Welding Machine

**Product price:**

**2,059.00 € tax excluded**

**Product description:**

## **PRAMAC W220 TDC ENGINE-DRIVEN WELDER 5.5 kW**

PRAMAC W220 TDC is a light, compact engine-driven welder, equipped with a Honda GX390 recoil gasoline engine capable of delivering 5.5 kW.

PRAMAC engine-driven welders are the ideal choice for small repairs or more demanding craft applications. With 220 A output, you can use rutile, basic, or cellulosic electrodes up to 5 mm in diameter.

Mechanical adjustment of welding current.

Reliability, sturdiness, and low noise to meet every need.

### **Technical features PRAMAC W220 TDC:**

Single-phase max power: 2.4 kW

Single-phase continuous power: 2 kW

Three-phase max power: 5.5 kW

Three-phase continuous power: 4.16 kW

Fuel: Gasoline

Voltage: 230 V / 400 V

Frequency: 50 Hz



---

Engine: Honda GX390 (recoil)

Starting: Recoil

Welding current: 40–220 A

Welding voltage min/max: 21.6 V / 28.8 V

Electrode diameter: 5 mm

Consumption: 2.2 at 75% load

Length: 875 mm

Width: 620 mm

Height: 600 mm

Weight: 80 kg

If you are looking for a product with similar features, [CLICK HERE](#). You will find the entire dedicated category.

#### **Product features:**

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.4

Continuous power single phase (KW): 1.8

Maximum power single phase (KVA): 2.7

Continuous power single phase (KVA): 2.3

Maximum power three phase (KW): 5.5

Continuous power three phase (KW): 4.47

Maximum power three phase (KVA): 6.8

Continuous power three phase (KVA): 5.6

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Honda GX390 Recoil, naturally aspirated

Speed governor: Mechanical

Starting system: Pull starter

---



---

Engine capacity (cm<sup>3</sup>): 389

Oil capacity (L): 1.1

Cooling: Air

Protection degree: IP23

Welding current (A): 40-220

Welding voltage min/max (V): 21.6 / 28.8

Diameter electrodes (mm): 5

Fuel tank capacity (L): 6.1

Consumption (L/h): 0,8 al 75% del carico

Running time (h): 2.8 at 75% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 875

Width (mm): 620

Height (mm): 600

Dry weight (Kg): 80

Silenced: No

Super silenced: No

ATS Switch device : No

Voltage regulator: No

Engine manufacturer: Honda

