



AXO AEDE 12000TK Three Phase Diesel Generator Avr 14 KVA 11.2 KW

Product description:

The semi-silent eco Axo AEDE 12000TK generator is equipped with a 4-stroke twin cylinder air cooled diesel

engine (23 Hp). This is a handy portable generator for emergencies and household use.

The differential magneto-thermal switch provides protection against overloads, acting as a safeguard to protect operators against hazards.

The oil level indicator warns when the oil level is low. It also has an extra large silencer for even quieter operation.

The AVR regulator is able to provide stable voltage and current.

It has an instrument for digital electric control, analogue for the engine.

? Rated electric power output 12.0 kVA equivalent to 10.0 kW

? In the three-phase configuration you can obtain a third of the single-phase power on each phase

? In the three-phase configuration the single-phase power is further protected by a designated bipolar

magneto-thermal switch

The images are purely for information.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 3.68

Continuous power single phase (KW): 3.2

Maximum power single phase (KVA): 4.6

Continuous power single phase (KVA): 4

Maximum power three phase (KW): 11.2





Continuous power three phase (KW): 9.6
Maximum power three phase (KVA): 14
Continuous power three phase (KVA): 12
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 380V 16A 3P+N CE - 2 x 220V 16A SCHUKO
Engine: AMDE 2L290
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 954
Cooling: Air
Fuel tank capacity (L): 35
Consumption (L/h): 2.92
Running time (h): 12
Acoustic pressure: 79 dB(A) at 7 m
Length (mm): 900
Width (mm): 570
Height (mm): 800
Dry weight (Kg): 210
Silenced: Yes
Super silenced: No
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Axo

