



AXO AEDE 6001SM Silent Single Phase Avr Diesel Generator 5 KVA 4 KW

Product description:

The silent eco diesel Axo AEDE 6000SM generator is equipped with a centrifugal governor, single-phase alternator, THD (total harmonic distortion) value less than 6% and voltage accuracy between +2% and -2%.

The starting capability is 2 times the rated current.

Connection

220 V: N.2 SCHUKO sockets 16A

12 V DC: 2 screw type banana plugs one red (+) and one black (-)

Protections

Unipolar differential magneto-thermal switch.

10A fast fuse on the 12 V DC.

Reading instrument

Analogue voltmeter

Regulations

To connect to a compliant socket board.

Handling

Rubber wheel and fold-away handlebar kit.

Recommended use





Powerful electrical equipment, appliances and lighting that do not tolerate voltage variations between no load and full load and require a consistent voltage level.

Safe use

Before use, check the electrical requirements of the user and the maximum starting current of the loads.

The images are purely for information.

Product features:

Phase: Single phase

Maximum power single phase (KW): 4

Continuous power single phase (KW): 3.6

Maximum power single phase (KVA): 5

Continuous power single phase (KVA): 4.2

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x 220V 16A SCHUKO

Engine: AMDE 186

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm³): 418

Cooling: Air

Fuel tank capacity (L): 12.5

Consumption (L/h): 1.25

Running time (h): 10

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 735

Width (mm): 485

Height (mm): 670

Dry weight (Kg): 165

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Axo

