



AXO AEGE 6501T Three Phase Petrol Avr Generator 6.5 Kva 5.2 KW

Product description:

The semi-silent petrol Axo AEGE 6501T generator is equipped with a three-phase alternator with neutral available,

THD (total harmonic distortion) value less than 6% and voltage accuracy between +1.5% and -1.5%.

The starting capability is 2 times the rated current.

Connection

three-phase 380 V: N.1 CE socket, 16A three-phase 3P+N+E for full power

single-phase 220 V: N.1 SCHUKO socket 16A for 33% power

12 V DC: 2 screw type banana plugs one red (+) and one black (-)

Protections

4P differential magneto-thermal main switch.

10A fast fuse on the 12 V DC.

Reading instrument

Digital voltmeter for reading voltage

Regulations

Can be connected to a user with certification required

Recommended use

Powerful electrical equipment, appliances and lighting that do not tolerate voltage variations between no load





and full load and require a consistent voltage level.

Safe use

Before use, check the electrical requirements of the user and the maximum starting current of the loads with particular attention to the single-phase power source.

The pictures are for illustrative purposes only.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 1.76

Continuous power single phase (KW): 1.6

Maximum power single phase (KVA): 2.2

Continuous power single phase (KVA): 2

Maximum power three phase (KW): 5.2

Continuous power three phase (KW): 4.8

Maximum power three phase (KVA): 6.5

Continuous power three phase (KVA): 6

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 380V 16A 3P+N+T CE - 1 x 220V 16A SCHUKO

Engine: AMGE 390

Engine rpm (rpm): 3000

Starting system: Electric 12 Vcc / Manual

Engine capacity (cm³): 389

Cooling: Air

Fuel tank capacity (L): 25

Consumption (L/h): 1.56

Running time (h): 16

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 680

Width (mm): 540

Height (mm): 540

Dry weight (Kg): 83

Silenced: Yes

Super silenced: No

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Axo



