



AXO AEGE 8001M Petrol Single Phase Avr Generator 8 Kva 6.4 KW

Product description:

The semi-silent single-phase petrol Axo AEGE 8001M generator is equipped with a single-phase alternator, THD (total harmonic distortion) value less than 6% and voltage accuracy between +2% and -2%. The starting capability is 2 times the rated current.

Connection

220 V: N.1 SCHUKO socket 16A + N.1 CE socket, 32A 2P+E for full power
12 V DC: 2 screw type banana plugs one red (+) and one black (-)

Protections

Bipolar differential magneto-thermal switch.
10A fast fuse on the 12 V DC.

Reading instrument

Digital voltmeter for reading voltage

Regulations

Can be connected to a user with certification required

Recommended use

Low power electrical equipment, appliances and lighting that do not tolerate voltage variations between no load and full load and require a consistent voltage level.



Safe use

Before use, check the electrical requirements of the user and the maximum starting current of the loads.

The pictures are for illustrative purposes only.

Product features:

Phase: Single phase

Maximum power single phase (KW): 6.4

Continuous power single phase (KW): 5.6

Maximum power single phase (KVA): 8

Continuous power single phase (KVA): 7

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 220V 32A 2P+T CE - 1 x 220V 16A SCHUKO

Engine: AMGE 420

Engine rpm (rpm): 3000

Starting system: Electric 12 Vcc / Manual

Engine capacity (cm³): 420

Cooling: Air

Fuel tank capacity (L): 25

Consumption (L/h): 1.78

Running time (h): 14

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 680

Width (mm): 540

Height (mm): 540

Dry weight (Kg): 90

Silenced: Yes

Super silenced: No

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Axo

