



PRAMAC PX4000

Product price:

471,00 € tax excluded

Product description:

Product features:

Phase: Single phase

Maximum power single phase (KW): 2.7

Continuous power single phase (KW): 2.3

Maximum power single phase (KVA): 3

Continuous power single phase (KVA): 2.5

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x 230V 16A IP54 SCHUKO

Engine: PRAMAC AP170F, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Pull starter

Engine capacity (cm³): 208

Oil capacity (L): 0.6

Cooling: Air

Poles: 2

Fuel tank capacity (L): 18.5

Consumption (L/h): 0.96 at 75% of the load / 1.29 at 100% of the load

Running time (h): 19.27 at 75% of the load / 14.34 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 600

Width (mm): 439

Height (mm): 588



Dry weight (Kg): 53

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: PRAMAC

Video: 0FlbtCzOIWA