



PRAMAC PX3250

Product price:

600,00 € tax excluded

Product description:

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.6

Continuous power single phase (KW): 2.7

Maximum power single phase (KVA): 4

Continuous power single phase (KVA): 3

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: PRAMAC AP188F, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Pull starter

Engine capacity (cm³): 389

Oil capacity (L): 1.1

Cooling: Air

Poles: 2

Fuel tank capacity (L): 25.5

Consumption (L/h): 1.43 at 75% of the load / 1.92 at 100% of the load

Running time (h): 17.71 at 75% of the load / 13.28 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 73 dB(A) at 7 m

Length (mm): 727

Width (mm): 515

Height (mm): 670





Dry weight (Kg): 79

Silenced: No

Super silenced: No

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: PRAMAC

