



# PRAMAC PX8000 SINGLE-PHASE GENERATOR 6 KVA AVR

Product price:

**965.14 € tax excluded**

## Product description:

### PRAMAC PX8000 SINGLE-PHASE GENERATOR 6 KVA AVR

PRAMAC PX8000 single-phase generator with Pramac SR190F gasoline engine, capable of delivering a power of 6 KVA, complete with AVR voltage regulator.

The PRAMAC PX8000 generator is equipped with electric start with battery, but it is also provided with a rope recoil starter for manual start. The generator alternator is with AVR voltage regulator.

The gasoline engine Pramac SR190F makes the genset very reliable as it has been built and designed using high quality materials.

Due to its very low weight and compact size, it is convenient to carry where you need it most. This generator is suitable for outdoor use in small construction sites or for small outdoor work for hobby use.

The PRAMAC PX8000 represents one of the latest innovations of Pramac to ensure a high level of quality and performance at an attractive price. PRAMAC PX8000 generator is compact, efficient and easy to use.

## TECHNICAL FEATURES PRAMAC PX8000:

Phase type: Single-phase

Single-phase continuous power: 5 KVA / 4.5 KW

Maximum single-phase power: 6 KVA / 5.4 KW

Motor: Pramac SR190F

Motor speed: 3000 rpm

Emissions regulations: Not emitted

Starter: Electric / Manual

Fuel: Petrol



Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 1 x SCHUKO 230V 16A / 1 x 2P+E CEE 230V 16A / 1 x 2P+E CEE 230V 32A  
Tank capacity: 27 l  
Acoustic pressure: 69 dB(A) @ 7 m  
Length: 727 mm  
Width: 515 mm  
Height: 670 mm  
Dry weight: 94 kg  
Displacement cm<sup>3</sup>: 420  
Autonomy at 75% load h 13.50  
Autonomy at 100% load h 10.15

### CONTROL PANEL

Controls:

- Start key: OFF - ON - START

Instrumentation:

- Voltmeter
- Ammeter
- Frequency meter
- Fuel level indicator

Protections:

- Thermal Protection
- Oil Guard (low oil level)

Sockets

- N.1 SCHUKO 230V 16A IP54
- N.1 2P+T CEE 230V 16A IP44
- N.1 2P+T CEE 230V 32A IP44

Are you looking for a generator with different technical features? [HERE](#) you can find the area dedicated to PRAMAC generator or other specialized brands.

Images and technical data are not binding.

### Product features:

Phase: Single phase

---



Maximum power single phase (KW): 5.4  
Continuous power single phase (KW): 4.5  
Maximum power single phase (KVA): 6  
Continuous power single phase (KVA): 5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: PRAMAC SR190F, naturally aspirated  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 3000  
Speed governor: Mechanical  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 420  
Oil capacity (L): 1.1  
Cooling: Air  
Poles: 2  
Fuel tank capacity (L): 27  
Consumption (L/h): 2.75  
Running time (h): 9.8  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 727  
Width (mm): 515  
Height (mm): 670  
Dry weight (Kg): 97  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: PRAMAC

