



Shop name



PRAMAC P11000

Generator Set Single-phase

9.7KW AMF

Product price:

6,550.19 € tax excluded

Product description:

PRAMAC P11000 SINGLE-PHASE GENERATOR 9.7KW

The PRAMAC P11000 single-phase generator delivers 9.7 kW of power with a diesel engine running at 3000 rpm. The PRAMAC P11000 generator is equipped with electric start. Its alternator is fitted with a capacitor voltage regulator. The Yanmar diesel engine makes the PRAMAC P11000 highly reliable, as it has been built and designed using top-quality materials. With its compact dimensions, it can be easily handled and transported. The PRAMAC P11000 single-phase generator is suitable for outdoor use in small construction sites or for light-duty applications.

Technical specifications of the PRAMAC P11000 AMF single-phase generator:

Maximum Single-phase Power: 9.7 kW
Continuous Single-phase Power: 9 kW
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Engine: Yanmar 3TNV70-HGE
Starting: Electric
Fuel Consumption: 3.97 L/h at 100% load
Length: 1400 mm
Width: 650 mm
Height: 975 mm
Weight: 325 kg

CONTROL PANEL

Controls:

- Ignition key: OFF - ON - START

Instrumentation:



- Voltmeter
- Hour counter
- Low oil pressure indicator

Protections:

- Circuit breaker
- Automatic with transfer switch (AMF)

Outlets:

- 2 x 2P+T CEE 230V 16A IP44
- 1 x 2P+T CEE 230V 32A IP44

The PRAMAC P11000 generator is a professional diesel genset developed by Pramac, featuring a soundproofed canopy design, making it ideal for use in residential areas. Thanks to its low noise level, the PRAMAC P11000 is the perfect solution for residential use or outside working hours. The P11000 generator is equipped with high-quality components and complete instrumentation, suitable for construction sites or as a backup power source during blackouts.

If you are looking for a generator like the PRAMAC P11000 AMF single-phase model, we recommend browsing our catalog of [land-based generators](#) to find the one that best suits your needs.

Product features:

Phase: Single phase

Maximum power single phase (KW): 9.7

Continuous power single phase (KW): 9

Maximum power single phase (KVA): 10.8

Continuous power single phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE

Engine: Yanmar 3TNV70-HGE, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 854

Oil capacity (L): 3.8

Cooling: Water

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 3.04 at 75% of the load / 3.96 at 100% of the load



Running time (h): 7.87 at 75% of the load / 6.05 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 1400

Width (mm): 650

Height (mm): 975

Dry weight (Kg): 325

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Yes

Voltage regulator: Capacitor

Engine manufacturer: Yanmar