



# PRAMAC P11000 THREE PHASE AMF



## Product description:

## Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 5.28

Continuous power single phase (KW): 4.8

Maximum power single phase (KVA): 6.6

Continuous power single phase (KVA): 6

Maximum power three phase (KW): 8.6

Continuous power three phase (KW): 8

Maximum power three phase (KVA): 10.8

Continuous power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE

Engine: Yanmar 3TNV70-HGE, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 854

Oil capacity (L): 3.8

Cooling: Water

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 2.65 at 75% of the load / 3.45 at 100% of the load

Running time (h): 9.06 at 75% of the load / 6.96 at 100% of the load





---

Acoustic power: 96 dB(A)  
Acoustic pressure: 68 dB(A) at 7 m  
Length (mm): 1400  
Width (mm): 650  
Height (mm): 975  
Dry weight (Kg): 325  
Silenced: Yes  
Super silenced: No  
Product type: Generator  
ATS Switch device : Yes  
Voltage regulator: Compound  
Engine manufacturer: Yanmar