



PRAMAC P12000 GENERATOR 12KVA SINGLE PHASE STAGE V AVR

Product price:

3.540,00 € tax excluded

Product description:

PRAMAC P12000 GENERATOR 12KVA SINGLE PHASE STAGE V AVR

Pramac P12000 Single-phase generator equipped with Honda GX630 StageV gasoline engine, deliver a maximum power of 12 KVA, with AVR voltage regulator.

The single-phase PRAMAC P12000 is a powerful and reliable solution with a power output of 13KVA, powered by a gasoline engine at a speed of 3000 RPM. This generator offers superior performance thanks to the Honda gasoline engine and the built-in electric starter, ensuring a quick and effortless start.

The alternator of the PRAMAC P12000 is equipped with an AVR voltage regulator, which stabilizes the output voltage and prevents undesirable fluctuations. This contributes to providing stable and reliable energy to connected devices. Built with high-quality materials, the Honda gasoline engine confers significant reliability and durability to the generator.

The presence of a specially designed enclosure makes the PRAMAC P12000 a super-silent generator, ideal for use in noise-sensitive environments. Its versatility makes it suitable for outdoor applications, such as small construction sites or external works. The generator features a robust structure that guarantees durability and resilience.

This PRAMAC P12000 is designed with professional features and high-quality components, resulting in a superior-class product. Its exceptional silence makes it particularly suitable for use in residential areas or contexts where noise needs to be minimized, such as during resting hours.

Incorporating a reliable gasoline engine, high-quality components, and comprehensive instrumentation, the PRAMAC P12000 AVR is capable of delivering reliable and consistent performance in various situations. In conclusion, this generator represents an ideal solution for

those seeking an efficient and reliable power source across diverse applications.

Automatic Starting Panel ATS (Optional)

The Pramac P12000 is equipped for use with an automatic ATS starting panel. With this feature, you no longer need to worry about blackouts, as if the power supply is interrupted, this panel can automatically start the generator, allowing you to continue your activities without losing your work data.

StageV Emission Regulations

The PRAMAC P12000 is equipped with a StageV "mobile" engine, as required by European Regulation 2016/1628. These new engines significantly reduce particle and nitrogen oxide emissions emitted by the generator into the environment, ensuring a 200% reduction in environmental impact compared to standard engines.

Technical Specifications of PRAMAC P12000

Phase Type: Single-Phase

Continuous Power: 10.0 KVA / 9.1 KW

Maximum Power: 11.9 KVA / 10.7 KW

Voltage VAC: 230 V

Frequency (Hz): 50

Voltage Regulator: AVR

Starting: Electric

Engine: Honda GX630

RPM: 3000

Emission Regulation: StageV

Fuel: Gasoline

Outlet Panel: 1 x SCHUKO 230V 16A IP54 - 1 x CEE 230V 16A 2P - 2 x CEE 230V 32A 3P

Tank Capacity: 24 l

Consumption @ 75% load: 4.07 l/h

Autonomy @ 50% load: 5.90 h

Sound Pressure: 61 dB(A) @ 7m

Length: 990 mm

Width: 602 mm

Height: 826 mm

Net Weight: 188 Kg

Looking for a product with different technical specifications? [HERE](#) you can find the dedicated area for Pramac generators or other specialized brands.

The images are purely indicative.



Product features:

Phase: Single phase

Maximum power single phase (KW): 10.7

Continuous power single phase (KW): 9.1

Maximum power single phase (KVA): 11.9

Continuous power single phase (KVA): 10

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Honda GX630, naturally aspirated

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 688

Oil capacity (L): 1.9

Cooling: Air

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 4.07 at 75% of the load / 5.43 at 100% of the load

Running time (h): 5.90 at 75% of the load / 4.42 at 100% of the load

Acoustic power: 89 dB(A)

Acoustic pressure: 61 dB(A) at 7 m

Length (mm): 990

Width (mm): 602

Height (mm): 826

Dry weight (Kg): 188

Inverter: No

AVR: Yes

Compound: No

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

