



PRAMAC P12000 THREE PHASE DPP AVR

Product price:

3.635,00 € tax excluded

Product description:

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 3.68
Continuous power single phase (KW): 3.2
Maximum power single phase (KVA): 4.6
Continuous power single phase (KVA): 4
Maximum power three phase (KW): 11.1
Continuous power three phase (KW): 9.5
Maximum power three phase (KVA): 13.9
Continuous power three phase (KVA): 11.8

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A

SCHUKO

Engine: Honda GX630, naturally aspirated

Engine rpm (rpm): 3000 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 688

Oil capacity (L): 1.9

Cooling: Air Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 4.23 at 75% of the load / 5.63 at 100% of the load Running time (h): 5.67 at 75% of the load / 4.26 at 100% of the load





Acoustic power: 89 dB(A)

Acoustic pressure: 61 dB(A) at 7 m

Length (mm): 990 Width (mm): 602 Height (mm): 826 Dry weight (Kg): 188

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

