



# PRAMAC P12000 THREE PHASE DIESEL IPP



## Product description:

## Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 9.5

Continuous power single phase (KW): 6.8

Maximum power single phase (KVA): 9.1

Continuous power single phase (KVA): 8.5

Maximum power three phase (KW): 12.6

Continuous power three phase (KW): 9.6

Maximum power three phase (KVA): 15.8

Continuous power three phase (KVA): 12

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE

Engine: Hatz 2G40, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 997

Oil capacity (L): 2.5

Cooling: Air

Poles: 2

Fuel tank capacity (L): 17

Consumption (L/h): 2.74 at 75% of the load / 3.66 at 100% of the load

Running time (h): 6.20 at 75% of the load / 4.64 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1270



Width (mm): 610

Height (mm): 816

Dry weight (Kg): 275

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Hatz

