



# PRAMAC P3000i SINGLE-PHASE GENERATOR 2.5 KW INVERTER

Product price:

**698,00 € tax excluded**

## Product description:

### PRAMAC P3000i SINGLE-PHASE GENERATOR 2.5 KW INVERTER

The PRAMAC P3000i single-phase generator is equipped with an Pramac OHV petrol engine, delivers a power of 2,5 KW and is equipped with **Inverter voltage regulator**.

The PRAMAC P3000i is among the quietest in its class as it has been designed with soundproofing coatings and the exclusive silencer of the exhaust system.

Designed with lightweight materials to enhance portability and ergonomically designed, this portable power generator is extremely easy to lift and carry.

The voltage regulator with inverter technology guarantees you a constant, clean and uninterrupted supply of electricity. In this way, thanks to the inverter, **you can connect your sensitive devices to your generator** (PCs, smartphones, appliances, etc.) in complete safety and without burning them.

PRAMAC P3000i can be connected together by means of a parallel cable that doubles the power. Connected in this way, they can **meet the needs of small structures** such as supplying electricity to ensure the operation of the air conditioner in a camper. Two smaller gensets are easier to handle and transport than a large one, and once in place they can be connected to increase power.

## TECHNICAL FEATURES PRAMAC P3000i

Type of phase: Single-phase

Continuous power: 2.3 KVA / 2.3 KW

Maximum power: 2.5 KVA / 2.5 KW

Engine: Pramac OHV

Engine revolutions: 3000 rpm



Emissions regulations: Not emitted  
Starting: Tear-off with recoil  
Fuel: Petrol  
Voltage: 230 V  
Frequency: 50 Hz  
Sockets panel: 2 x SCHUKO 230V 16A  
Voltage regulator: Inverter  
Tank capacity: 4 l  
Consumption at 75% of the load: 1.14 l / h  
Autonomy at 75% of the load: 3.5 h  
Acoustic pressure: 61 dB (A) @ 7 m  
Length: 565 mm  
Width: 339 mm  
Height: 467 mm  
Dry weight: 27 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) You can find the area dedicated to specialized brand generators.

The image is purely indicative.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 2.5  
Continuous power single phase (KW): 2.3  
Maximum power single phase (KVA): 2.5  
Continuous power single phase (KVA): 2.3  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 x 230V 16A SCHUKO  
Engine: OHV  
Speed governor: Electronic  
Starting system: Pull starter with recoil  
Number cylinders: 1  
Cooling: Air  
Fuel tank capacity (L): 4  
Consumption (L/h): 1.14 at 75% load  
Running time (h): 3.5 at 75% load  
Acoustic power: 88 dB(A)  
Acoustic pressure: 61 dB(A) at 7 m  
Length (mm): 565





Width (mm): 339  
Height (mm): 467  
Dry weight (Kg): 27  
Inverter: Yes  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : No  
Voltage regulator: Inverter  
Engine manufacturer: PRAMAC