



PRAMAC P6000s SINGLE PHASE

Product price:

4,301.37 € tax excluded

Product description:

PRAMAC P6000s Single-phase 5.4 KW Super Silent Generator

The PRAMAC P6000s single-phase generator has a power output of 5.4 KW, powered by a diesel engine running at 3000 RPM. The PRAMAC P6000s generator is equipped with electric start. The alternator of the PRAMAC P6000s generator features a capacitor voltage regulator. The Yanmar diesel engine makes the P6000s generator very reliable as it is built and designed using high-quality materials.

Thanks to its casing, it can be considered super silent, and with its compact dimensions, it can be easily handled and transported. The PRAMAC P6000s single-phase generator is suitable for outdoor use in small construction sites or for small outdoor jobs.

Technical features of the PRAMAC P6000s Single-phase generator:

Maximum Single-phase Power: 5.4 KWContinuous Single-phase Power: 4.4 KW

Fuel: DieselVoltage: 230 VFrequency: 50 Hz

- Engine: Yanmar L100N Electric

- Starting System: Electric

- Consumption: 1.94 Lt/h at 100% load

Length: 970 mmWidth: 580 mmHeight: 927 mmWeight: 203 Kg

CONTROL PANEL



Controls:

- Start Key: OFF ON START
- Connector for automatic AMF/RSS panel

Instrumentation:

- Voltmeter

Protections:

- Circuit Breaker
- Differential Protection (DPP)
- Engine Protection Board: Low oil pressure; High engine temperature; Fuel reserve; Battery charge fault

Outlets:

- N.1 SCHUKO 230V 16A IP54
- N.1 2P+T CEE 230V 16A IP44
- N.1 2P+T CEE 230V 32A IP44

The PRAMAC P6000s power generator is a professional diesel generator developed by Pramac with a diesel engine in a soundproofed and enclosed version, ideal for use in residential areas. The PRAMAC P6000s power generator, with its quiet operation, is the ideal generator for use in residential areas or outside working hours.

The P6000s generator is equipped with top-quality components, complete with protections and instrumentation.

If you are looking for a generator like the P6000s single-phase power generator, we recommend browsing our catalog of land-based generators to find the one that best suits your needs.

Images and technical data are non-binding.



Product features:

Phase: Single phase

Maximum power single phase (KW): 5.4 Continuous power single phase (KW): 4.4 Maximum power single phase (KVA): 5.9 Continuous power single phase (KVA): 4.9

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A

SCHUKO

Engine: Yanmar L100N Electric, naturally aspirated

Engine rpm (rpm): 3000 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 435

Oil capacity (L): 1.6

Cooling: Air Poles: 2

Fuel tank capacity (L): 19

Consumption (L/h): 1.45 at 75% of the load / 1.94 at 100% of the load Running time (h): 13.10 at 75% of the load / 9.79 at 100% of the load

Acoustic power: 84 dB(A)

Acoustic pressure: 56 dB(A) at 7 m

Length (mm): 970 Width (mm): 580 Height (mm): 927 Dry weight (Kg): 203

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: Optional Voltage regulator: Capacitor Engine manufacturer: Yanmar

