



# PRAMAC P6000s THREE PHASE DPP

**Product price:**

**3.865,00 € tax excluded**

## **Product description:**

### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 2.56

Continuous power single phase (KW): 2.4

Maximum power single phase (KVA): 3.2

Continuous power single phase (KVA): 3

Maximum power three phase (KW): 5.5

Continuous power three phase (KW): 4.5

Maximum power three phase (KVA): 6.9

Continuous power three phase (KVA): 5.6

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar L100N Electric, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 435

Oil capacity (L): 1.6

Cooling: Air

Poles: 2

Fuel tank capacity (L): 19

Consumption (L/h): 1.46 at 75% of the load / 1.94 at 100% of the load

Running time (h): 13.01 at 75% of the load / 9.79 at 100% of the load



Acoustic power: 84 dB(A)  
Acoustic pressure: 56 dB(A) at 7 m  
Length (mm): 970  
Width (mm): 580  
Height (mm): 927  
Dry weight (Kg): 203  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: Compound  
Engine manufacturer: Yanmar