



PRAMAC P9000 THREE PHASE DPP AVR

Product price:

5,811.53 € tax excluded

Product description:

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 4.32 Continuous power single phase (KW): 4 Maximum power single phase (KVA): 5.4 Continuous power single phase (KVA): 5 Maximum power three phase (KW): 8.5 Continuous power three phase (KW): 7.3 Maximum power three phase (KVA): 10.6 Continuous power three phase (KVA): 9.1

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A

SCHUKO

Engine: Lombardini 25LD330, naturally aspirated

Engine rpm (rpm): 3000 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 654

Oil capacity (L): 1.8

Cooling: Air

Alternator: Brushless

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 2.18 at 75% of the load / 2.91 at 100% of the load Running time (h): 11.01 at 75% of the load / 8.25 at 100% of the load

Acoustic power: 97 dB(A)



Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 990 Width (mm): 602 Height (mm): 826 Dry weight (Kg): 207

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Lombardini

