



WFM SE12000-MTHE AVR

Product description:

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 8.8

Continuous power single phase (KW): 7.9

Maximum power single phase (KVA): 11

Continuous power single phase (KVA): 9.9

Maximum power three phase (KW): 26.4

Continuous power three phase (KW): 24

Maximum power three phase (KVA): 33

Continuous power three phase (KVA): 30

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: John Deere 3029 DF 128, naturally aspirated

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 2900

Number cylinders: 3

Cooling: Water

Alternator: Mecc Alte ECO 28 VL4, brushless

Poles: 4

Bore x stroke (mm): 106 x 110

Fuel tank capacity (L): 135

Consumption (L/h): 7 at 100% of the load

Running time (h): 19.28 at 100% of the load

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 1940



Width (mm): 1000

Height (mm): 1480

Dry weight (Kg): 960

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: John Deere

