



GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

Product price:

3,156.00 € tax excluded

Product description:

GENSET MG 8000 BS/HA SINGLE-PHASE POWER GENERATOR 7 KVA AVR

GENSET MG 8000 BS/HA Single-phase generating set with Honda GX 390 OHV STAGE V engine powered by gasoline, capable of delivering a maximum power of 7 KVA complete with AVR voltage regulator.

The GENSET MG 8000 BS/HA generator set is compact and easy to use, equipped with a casing that lowers noise emissions and makes it super-silenced.

The GENSET MG 8000 BS/HA is equipped with electric start with 12 V battery and low fuel consumption, in fact it consumes only 3.3 liters/hour at 75% load.

The generator set GENSET MG 8000 BS/HA is part of the silenced series and are characterized by lower consumption and a longer life expectancy than the range powered by gasoline and equipped with soundproof cabin suitable for installation and outdoor use, and increased tank. The GENSET MG 8000 BS/HA generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 continuous hours and for more than 500 hours per year.

TECHNICAL FEATURES GENSET MG 8000 BS/HA

Phase Type: Single-Phase

Maximum Single-Phase Power: 7 KVA / 5.6 KW

VAC Voltage: 230 / 400 V

Frequency (Hz): 50

Quadro Starter: Manual with self-winding

Motor: Honda GX 390 OHV Emission Standard: STAGEV

RPM: 3000

Power supply: Gasoline



Fuel tank capacity: 10.5 l

Consumption @ 75 % load: 3.3 l/h Autonomy @ 75 % load: 3.18 h Sound pressure: 86 dB(A)

Length: 1059 mm Width: 670 mm Height: 740 mm Net weight: 138 Kg

Are you looking for a generator with different technical characteristics? <u>Here</u> you can find the full range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.6 Maximum power single phase (KVA): 7

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE

Engine: Honda GX390, 4 stroke, OHV

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 390

Number cylinders: 1

Cooling: Air

Alternator: Synchronous Protection degree: IP23 Motor insulation class: H Fuel tank capacity (L): 10.5 Consumption (L/h): 3.3 Running time (h): 3.18 Acoustic power: 86 dB(A)

Acoustic pressure: 61 dB(A) at 7 m

Length (mm): 1059 Width (mm): 670



Height (mm): 740 Dry weight (Kg): 138 Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda

