



GENSET MG 6000 S-Y -GENERATOR 6.25 KVA

Product price:

3,234.08 € tax excluded

Product description:

GENSET MG 6000 S-Y SINGLE PHASE GENERATOR 6,3KVA

GENSET MG 6000 S-Y Singlephase generating with Yanmar L100V diesel engine, capable of delivering a maximum power of 6,3KVA, complete with optional AVR voltage regulator.

The GENSET MG 6000 S-Y is compact and easy to use, equipped with a casing that lowers noise emissions and makes it super-silenced.

The GENSET MG 6000 S-Y is a 6,3KVA singlephase diesel generator set with electric start. This generator is also available in a version with AVR voltage regulator, with automatic panel and remote control.

The GENSET MG 6000 S-Y generator set includes:

- Voltmeter
- Hour meter
- Differential magnetothermic switch
- Emergency stop button
- Starting battery
- 1 singlephase socket CEE 32A, 230V 50 Hz
- 1 singlephase socket CEE 16A, 230V 50 Hz
- Protection for outputs
- Arrangement for operation in AMF/ATS or Remote control
- Central lifting hook

TECHNICAL FEATURES GENSET MG 6000 S-Y

Phase Type: SinglePhase

Maximum SinglePhase Power: 6,3KVA / 5.04 KW

VAC Voltage: 230 V Frequency (Hz): 50



Quadro Starter: Electric Engine: Yanmar L100V

Emissions Standard: Non-emitting

RPM: 3000

Power supply: Diesel Fuel tank capacity: 10.5 l

Consumption @ 75 % load: 1.5 l/h

Autonomy @ 75 % load: 7 h Sound pressure: 97 dB(A)

Length: 815 mm Width: 560 mm Height: 730 mm Net weight: 150 Kg

Are you looking for a generator with different technical characteristics? <u>Here</u> you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5 Maximum power single phase (KVA): 6.3

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE

Engine: Yanmar L100N, 4 stroke

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 435

Number cylinders: 1

Cooling: Air

Alternator: Synchronous Protection degree: IP23 Motor insulation class: H Fuel tank capacity (L): 10.5 Consumption (L/h): 1.5 Running time (h): 7

Acoustic power: 97 dB(A)

Acoustic pressure: 72 dB(A) at 7 m



Length (mm): 815 Width (mm): 560 Height (mm): 730 Dry weight (Kg): 150

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: Optional Voltage regulator: AVR (optional) Engine manufacturer: Yanmar

