



GENSET MG 6001 SS-Y - GENERATOR 6 KVA

Product price:

3,755.35 € tax excluded

Product description:

GENSET MG 6001 SS-Y SINGLE PHASE GENERATOR 6KVA

GENSET MG 6001 SS-Y Singlephase generating with Yanmar L100V diesel engine, capable of delivering a maximum power of 6KVA.

The GENSET MG 6001 SS-Y generator is compact and easy to use, equipped with enclosure that lowers noise emissions and makes it super-silenced.

The GENSET MG 6001 SS-YY is a 6KVA single-phase diesel generator with electric start. This generator is also available in a version with automatic panel and remote control.

Thanks to its compact size and very low weight, the MG 6001 SS-Y is a lightweight generator that is easy to transport. The GENSET MG 6001 SS-Y also has a low fuel consumption: only 1.5 Lt/h at 75% of the load.

The GENSET MG 6001 SS-Y generator set, thanks to the high quality and efficiency of its components, is ideal for various types of work: from small hobby work to large construction sites.

The MG 6001 SS-Y generator is ideal for various types of work: from small hobby work to large construction sites.

The generating set GENSET MG 6001 SS-Y includes:

- Automatic engine stop device with warning lights for:
- Battery charge failure
- Battery failure battery charge failure
- low fuel level
- low oil pressure
- Built-in 12 V battery



- 1 single-phase socket CEE 230V 32A
- 1 single-phase socket CEE 230V 16A
- Protections for power outputs
- Emergency differential switch
- Emergency stop button
- Fuel level indicator
- Hour meter
- Central lifting hook
- Ready for operation in AMF-ATS or Remote Control

Phase Type: SinglePhase

Maximum SinglePhase Power: 6 KVA / 4.8 KW Continuous SinglePhase Power: 5.4 KVA / 4.3 KW

VAC Voltage: 230 V Frequency (Hz): 50 Starting Frame: Electric Motor: Yanmar L100V

Emission Standard: Stage V

RPM: 3000

Power supply: Diesel Fuel tank capacity: 30 l

Consumption @ 75 % of load: 1.5 l/h Autonomy @ 75 % of load: 20 h Sound pressure: 92 dB(A)

Length: 1160 mm Width: 631 mm Height: 872 mm Net weight: 200 Kg

Are you looking for a generator with different technical characteristics? <u>Here</u> you can find the whole range of GENSET or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.4 Continuous power single phase (KW): 4.32 Maximum power single phase (KVA): 6 Continuous power single phase (KVA): 4.8

Fuel: Diesel

Frequency (Hz): 50



Voltage (V): 230

Sockets configuration: 1 x 230V 16A CEE - 1 x 230V 32A CEE - 1 x 110V 16A CEE - 1 x 110V

32A CEE

Engine: Yanmar L100V, 4 stroke Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 435

Number cylinders: 1

Cooling: Air

Protection degree: IP23 Motor insulation class: H Fuel tank capacity (L): 30 Consumption (L/h): 1.5 Running time (h): 20 Acoustic power: 92 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 1160 Width (mm): 631 Height (mm): 872 Dry weight (Kg): 200

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: Optional

Voltage regulator: No

Engine manufacturer: Yanmar

