



# GENSET MG 10/8 SS-K - SINGLE-PHASE/THREE-PHASE GENERATOR 10 KVA

Product price:

**6.277,60 € tax excluded**

## Product description:

GENSET MG 10/8 SS-K SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/8 SS-K is a singlephase / threephase generating equipped with a Kubota D722 (STAGE V) Diesel engine, capable of delivering a maximum power of 10KVA.

The GENSET MG 10/8 SS-K provides reliable power for home, business and recreational environments, safely powering appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop with clear, intuitive controls. The GENSET MG 10/8 SS-K is powered by a Kubota D722 **STAGE V** Diesel engine. These are very reliable engines that guarantee efficient combustion and low fuel consumption, and are also equipped with a protection system that causes the engine to stop if the oil level is too low.

The GENSET MG 10/8 SS-K has an all-steel construction and a large metal tank. The generator set guarantees an efficient and silent operation thanks to the Kubota D722 which allows to deliver a maximum power of 10 KVA.

The generator GENSET MG 10/8 SS-K comes with:

- Battery 12 V
- 1 threephase socket CEE 400V - 16A
- 1 singlephase socket CEE 230V - 32A
- 1 singlephase socket CEE 230V - 16A
- Thermal protection 16A
- Thermal protection
- Differential switch



- Emergency stop button
- Voltage selector
- Voltmeter
- Hour meter
- Central lifting hook
- Arrangement for operation in AMF-ATS or Remote control
- Glow plugs preheating warning light
- Automatic engine stop device with warning lights for:
  - battery failure
  - high water temperature
  - low oil pressure
  - low fuel level

#### TECHNICAL FEATURES GENSET MG 10/8 SS-K

Phase Type: SinglePhase/ThreePhase

Maximum SinglePhase Power: 6 KVA / 4.8 KW

Maximum ThreePhase Power: 10 KVA / 8 KW

VAC Voltage: 230 / 400 V

Frequency (Hz): 50

Quadro Starter: Electric

Motor: Kubota D722

Emission Standard: Stage V

RPM: 3000

Power supply: Diesel

Fuel tank capacity: 30 l

Consumption @ 75 % load: 3.3 l/h

Autonomy @ 75 % load: 9.09 h

Acoustic pressure: 95 dB(A)

Length: 1360 mm

Width: 675 mm

Height: 860 mm

Net weight: 350 Kg

Are you looking for a generator with different characteristics? Here you can find the full range of GENSET products or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

#### Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 4.8





---

Maximum power single phase (KVA): 6  
Maximum power three phase (KW): 8  
Maximum power three phase (KVA): 10  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE  
Engine: KUBOTA D722, 4 stroke  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 719  
Number cylinders: 3  
Cooling: Water  
Alternator: Synchronous  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 30  
Consumption (L/h): 3.3  
Running time (h): 9.09  
Acoustic power: 90 dB(A)  
Acoustic pressure: 65 dB(A) at 7 m  
Length (mm): 1360  
Width (mm): 675  
Height (mm): 860  
Dry weight (Kg): 350  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: Compound  
Engine manufacturer: Kubota

