

MASE MARINER 2800 S SINGLE PHASE MARINE GENERATOR SILENCED 30KW

Product description:

Ø.

MASE MARINER 2800 S SILENCED SINGLE-PHASE MARINE GENERATOR 30 KW EPA

MASE MARINER2800S single phase silenced marine generator is equipped with a YANMAR 4TNV98 diesel engine capable of delivering a maximum power of 30 KW at 1800 rpm.

The alternator of the generator is synchronous with 4 poles, self-regulated, self-excited, brushless, which in combination with the YANMAR engine can deliver a maximum power of 30 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the home.

The MASE MARINER2800S allows easy access for maintenance of the lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER2800S is equipped with a soundproof cabin that makes it super silent, with a sound emission of 56dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER2800S has innovative features that provide boat builders and end users with extreme ease of installation, high efficiency, high performance and quiet operation, while ensuring a very low level of environmental impact.

TECHNICAL FEATURES MASE MARINER2800S

Phase Type: Single Phase Maximum Power: 30 KW Fuel: Diesel Voltage: 120 - 240 V

PrestaShop

(R)

Frequency: 60 Hz Engine: YANMAR 4TNV98, 4 Stroke Emission Standard: Not Emitted Mechanical Power: 56 Hp Number of Cylinders: 4 Displacement: 3319 cc Engine RPM: 1800 rpm Fuel Consumption: 8. 9 l/h Sound pressure: 56 dB(A) @ 7 m Alternator: Synchronous Brushless Voltage regulator: AVR Length: 1295mm Width: 630 mm Height: 810 mm Weight: 595 Kg

Ø.

If you are looking for another marine generator then you can browse the entire catalog of marine generators.

Images and technical data are not binding.

Product features:

Phase: Single phase Maximum power single phase (KW): 30 Continuous power single phase (KW): 28 Fuel: Diesel Frequency (Hz): 60 Voltage (V): 120 / 240 Engine: Yanmar 4TNV98, 4 stroke Engine rpm (rpm): 1800 Speed governor: Centrifugal, mechanical Engine capacity (cm³): 3319 Number cylinders: 4 Oil capacity (L): 10.5 Cooling: Air Inyección : Direct Alternator: Synchronous, self-excited Poles: 4 Compression ratio: 18:1 Lubrication: Forced Consumption (L/h): 8.9 at 100% of the load Acoustic pressure: 56 dB(A) at 7 m

R

Length (mm): 1295 Width (mm): 630 Height (mm): 810 Dry weight (Kg): 595 Inverter: No AVR: Yes Compound: No Silenced: Yes Super silenced: Yes

R