



# MASE EA 5/3 GH GENERATOR 5,5KVA SINGLE PHASE/THREE PHASE STAGE V



## Product description:

### **MASE EA 5/3 GH THREE-PHASE GENERATOR 5.5KVA**

MASE EA 5/3 GH is a three-phase generator equipped with a Honda GX270 engine powered by gasoline, capable of delivering a maximum power of 5.5 KVA.

The MASE EA 5/3 GH three-phase generator provides reliable power for home, work and leisure environments, safely powering home appliances and other electronic devices.

The generator is as easy to install and operate as it is to start and stop thanks to clear, intuitive controls. MASE EA 5/3 GH is equipped with a honda GX270 gasoline engine. They are very reliable engines that provide efficient combustion and **low fuel consumption**. The engines with which the generators are equipped are also equipped with a protection system that causes the engine to stop if the oil level is too low.

MASE EA 5/3 GH is a stationary use machine, before commissioning, you must first secure the generator firmly to the ground. The MASE EA 5/3 GH are equipped with **6-liter tank** with a large cap that is convenient to unscrew even with work gloves

The generating set is composed of:

- 1 three-phase socket CEE 16 A, 400 V - 50 Hz protected by circuit breaker;
- 1 single-phase socket CEE 16 A, 230 V - 50 Hz protected by circuit breaker;
- Differential circuit breaker.

**On express request of the customer** is possible the additional supply of the transport trolley for the MASE EA 5/3 GH, the increased tank of 25 l and the AVR voltage regulator.

TECHNICAL CHARACTERISTICS MASE EA 5/3 GH



Maximum single-phase power: 2 KVA  
Maximum three-phase power: 5. 5 KVA  
Fuel: Gasoline  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Engine: Honda GX270 OHV  
Engine Revs: 3000  
Engine Displacement: 270 cm3  
Cooling: Air  
Starting: Manual  
Tank Capacity: 6 l  
Consumption: 2. 2 Lt/h at 75% load  
Acoustic power: 95 dB (70 dB at 7 m)  
Protection class: IP 23  
Length: 770 mm  
Width: 480 mm  
Height: 625 mm  
Weight: 80 kg

Are you looking for a power generator with different characteristics? [Here](#) you can find the full range of products MASE or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 1.6  
Maximum power single phase (KVA): 2  
Maximum power three phase (KW): 4.4  
Maximum power three phase (KVA): 5.5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A CEE - 1 x 230V 16A CEE  
Engine: Honda GX270, 4 stroke, OHV  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Ignition: Recoil  
Starting system: Manual  
Engine capacity (cm<sup>3</sup>): 270



Number cylinders: 1

Cooling: Air

Alternator: Synchronous

Fuel tank capacity (L): 6

Consumption (L/h): 2.2 at 75% of the load

Running time (h): 2.72 at 75% of the load

Acoustic power: 95 dB(A)

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 730

Width (mm): 480

Height (mm): 520

Dry weight (Kg): 80

Silenced: No

Super silenced: No

ATS Switch device : No

Voltage regulator: Compound / AVR (optional)

Engine manufacturer: Honda

