



MASE FX 50 H/A GENERATOR 4,5 KVA SINGLE PHASE STAGE V

Product price:

2,700.00 € tax excluded

Product description:

MASE FX 50 H/A GENERATOR 4.5 KVA SINGLE PHASE STAGE V

MASE FX 50 H/A is a single-phase generator, equipped with a Honda GX 270 **StageV** Gasoline-powered engine, it delivers a maximum power of 5,4KW.

The MASE FX 50 H/A provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

The generator is easy to install and operate, just as simple are starting and stopping thanks to the clear and intuitive controls. MASE FX 50 H/A is equipped with a Honda GX 270 petrol engine. They are very reliable engines that guarantee efficient combustion and **reduced fuel consumption**, they are also equipped with a protection system that causes the engine to stop if the oil level is too low.

STAGEV EMISSIONS REGULATION

MASE FX 50 H/A is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

Technical characteristics of MASE FX 50 H/A

Type of phase: Single-phase

Continuous power: 4 KVA / 3.2 KW Maximum power: 4.5 KVA / 3.6 KW



VAC voltage: 230 V Frequency (Hz): 50

Voltage regulator: Capacitor (AVR Optional)

Ignition panel: Electric Engine: Honda GX 270

Emissions standard: Stage V Revolutions per minute: 3000 rpm

Power supply: Gasoline

Sockets panel: 2 x CEE 16A 230V

Tank capacity: 5.3 l

Autonomy: 2.40 h at 75% of load Consumption: 2.2 l / h at 75% load Acoustic pressure: 74 dB (A) @ 7 m

Length: 725 mm Width: 515 mm Height: 585 mm Net weight: 78 Kg

Are you looking for a product with different technical characteristics? <u>HERE</u> you can find the area dedicated to MASE generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.6 Continuous power single phase (KW): 3.2 Maximum power single phase (KVA): 3.5 Continuous power single phase (KVA): 3.2

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 2 x 230V 16A CE

Engine: Honda GX270, 4 stroke Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 270

Number cylinders: 1

Cooling: Air

Alternator: Synchronous Fuel tank capacity (L): 6



Consumption (L/h): 2 at 75% of the load Running time (h): 3 at 75% of the load

Acoustic power: 99 dB(A)

Acoustic pressure: 74 dB(A) at 7 m

Length (mm): 725 Width (mm): 515 Height (mm): 585 Dry weight (Kg): 78

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Honda

