



MASE PD 40 Y GENERATOR 4,3KVA SINGLE PHASE STAGEV

Product price:

3.225,00 € tax excluded

Product description:

MASE PD 40 Y GENERATOR 4,3KVA SINGLE PHASE STAGEV

MASE PD 40 Y is a single-phase generator equipped with a diesel-supplied Yanmar L70V **StageV** engine, deliver a maximum power of 4,3KVA, complete with capacitor voltage regulator (**AVR optional**).

The generator is equipped with an electric start and has a low fuel consumption, in fact it consumes only 1 liters / hour at 75% of the load for an autonomy of up to 3.5 hours of operation.

MASE PD 40 Y provides reliable power for home, business and leisure environments Safely powering home appliances and other electronic devices Power solution for outdoor parties. Extremely practical sockets and controls make starting and operating easier, making these operations extremely simple and fast.

MASE PD 40 Y is equipped with a completely steel structure and a tank with a maximum capacity of 3.5 liters. The MASE PD 40 Y guarantees efficient and silent operation thanks to the Yanmar L70V StageV engine .

STAGEV EMISSIONS REGULATION

With the abbreviation STAGEV, the guidelines and the limits of the gas emissions of the engines are defined. The legislation is respected through the installation of special anti-particulate filters, but an indispensable condition for the filter to work properly is that the generating set works at its design temperature.

TECHNICAL CHARACTERISTICS OF MASE PD 40 Y

Type of phase: Single-phase

Continuous power: 3.5 KVA / 2.8 KW





Maximum power: 4.3 KVA / 3.4 KW

VAC voltage: 230 V Frequency (Hz): 50

Voltage regulator: Capacitor (AVR Optional)

Ignition panel: Electric Engine: Yanmar L70V

Emissions standard: Stage V Revolutions per minute: 3000 rpm

Fuel: Diesel

Socket panel: 2 x CEE 16A 230V

Tank capacity: 3.5 l

Autonomy: 3.5 h at 75% of load Consumption: 1 l / h at 75% load Acoustic pressure: 74 dB (A) @ 7 m

Length: 725 mm Width: 515 mm Height: 585 mm Net weight: 87 Kg

Are you looking for a product with different technical characteristics? HERE you can find the area dedicated to MASE generators and other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.4 Continuous power single phase (KW): 2.8 Maximum power single phase (KVA): 4.3 Continuous power single phase (KVA): 3.5

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 2 x 230V 16A CEE

Engine: Yanmar L70AE, 4 stroke Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 320

Number cylinders: 1

Cooling: Air

Alternator: Synchronous





Fuel tank capacity (L): 3.5

Consumption (L/h): 1 at 75% of the load

Running time (h): 3.5 at 75% of the load / 2.6 at 100% of the load

Acoustic power: 99 dB(A)

Acoustic pressure: 74 dB(A) at 7 m

Length (mm): 725 Width (mm): 515 Height (mm): 585 Dry weight (Kg): 87

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Yanmar

