



MASE MPV 16 BA

Product description:

OUT OF PRODUCTION

Single-phase maximum power: 11 KW
Three-phase maximum power: 12.8 KW
Three-phase continuous use power: 12 KW
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: Yanmar 3TNV88
Starting: Electric
Consumption: 2.5 Lt / h at 75% of the load
Length: 1750 mm
Width: 800 mm
Height: 900 mm
Weight: 600 Kg
Compound

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11
Maximum power single phase (KVA): 11
Maximum power three phase (KW): 12.8
Continuous power three phase (KW): 12
Maximum power three phase (KVA): 16
Continuous power three phase (KVA): 15
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 2 x 230V 16A CE



Engine: Yanmar 3TNV88, 4 stroke

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1642

Number cylinders: 3

Oil capacity (L): 6.7

Cooling: Water

Inyección : Direct

Alternator: Synchronous, self-excited

Poles: 4

Lubrication: Forced

Fuel tank capacity (L): 50

Consumption (L/h): 2.5 at 75% of the load

Running time (h): 20 at 75% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1750

Height (mm): 900

Dry weight (Kg): 600

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: Compound

Engine manufacturer: Yanmar

