



# MASE VOYAGER 6020 DM GENERATOR 7,5KVA VEHICULAR SINGLE PHASE AVR STAGEV

**Product price:** 

11,625.00 € tax excluded

## **Product description:**

# MASE VOYAGER 6020 DM 7.5KVA VEHICLE SINGLE-PHASE GENERATOR AVR STAGEV

MASE VOYAGER 6020 DM single-phase vehicle generator with diesel-powered Kubota Z482 **StageV** engine delivers a power of 7,5KVA, **complete with AVR voltage regulator**.

The MASE VOYAGER 6020 DM is designed with a soundproof booth that makes it **super silenced**. The soundproofing cabin of the MASE VOYAGER 6020 DM generator is made up of a supporting structure in aluminum profile which supports extremely light and extremely light 5754 painted marine aluminum panels with very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance interventions easier even with the generator installed in confined spaces.

#### **VOLTAGE REGULATOR AVR**

The purpose of the AVR, in a current generator, is to keep the output stable. And if its operation is very simple when resistive loads are fed, more complex is the matter in case of prevalently inductive loads: the delayed current opposes the inductor magnetic field, causing a voltage drop at the alternator output terminals; to compensate the phenomenon, the AVR intervenes automatically increasing the excitation current, until the output returns to the nominal value.

#### STAGEV EMISSIONS REGULATION

The MASE VOYAGER 6020 DM is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction of the environmental impact of 200% compared to standard



### engines.

#### TECHNICAL FEATURES MASE VOYAGER 6020 DM:

Phase type: Single-phase

Maximum Power: 7.5 KVA / 6 KW Continuous Power: 6.9 KVA / 5.5 KW

Fuel: Diesel Voltage: 230 V Frequency: 50 Hz Engine: Kubota Z482

Mechanical power: 11.1 Hp

Number of cylinders: 2 Displacement: 479 cc Engine rpm: 3000 rpm

Emissions standard: StageV

Consumption: 2.6 I / h at 75% load Acoustic power: 62 dBA @ 7 m

Voltage regulator: AVR

Length: 941 mm Width: 550 mm Height: 660 mm Weight: 190 Kg

Are you looking for a product with different technical characteristics? <u>HERE</u> you can find the area dedicated to MASE vehicle generators or other specialized brands.

Non-binding images and technical data.

### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 6 Continuous power single phase (KW): 5.5 Maximum power single phase (KVA): 7.5 Continuous power single phase (KVA): 6.9

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Engine: KUBOTA Z482, 4 stroke

Engine rpm (rpm): 3000

Speed governor: Centrifugal, mechanical

Starting system: Electric



Engine capacity (cm³): 479

Number cylinders: 2 Oil capacity (L): 2.5 Cooling: Water

Inyección: Indirect

Alternator: Sincrono, autoeccitato, autoregolato, senza spazzole

Poles: 2

Lubrication: Forced

Consumption (L/h): 2.6 at 75% of the load

Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 941 Width (mm): 550 Height (mm): 660 Dry weight (Kg): 190

Silenced: Yes

Super silenced: Yes Voltage regulator: AVR

