



MASE VOYAGER 15 DT GENERATOR 14KVA VEHICLE SINGLE-PHASE / THREE-PHASE AVR STAGEV

Product price:

18.637,50 € tax excluded

Product description:

MASE VOYAGER 15 DT GENERATOR 14KVA VEHICLE SINGLE-PHASE / THREE-PHASE AVR STAGEV

MASE VOYAGER 15 DM single / three-phase vehicle generator with diesel-powered Yanmar 3TNV88 **StageV** engine delivers a power of 14KVA, **complete with AVR voltage regulator**.

The MASE VOYAGER 15 DM vehicle generator is equipped with a soundproofing cabin that makes it super silenced, with a sound emission of 62dB (A) at a distance of 7 m. The painted aluminum soundproof booth is extremely light and highly resistant to external agents.

The soundproof cabin allows easy access for maintenance of the fuel and lubrication systems, the water pump, the air filter, the oil filter and the fuel.

MASE VOYAGER 15 DM is equipped with a ComAp InteliNano control unit that allows you to control and verify all the main functions of the unit and, if necessary, will report any failure or error in the operation of the machine.

STAGEV EMISSIONS REGULATION

The MASE VOYAGER 12 DM is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction of the environmental impact of 200% compared to standard engines.





TECHNICAL FEATURES MASE VOYAGER 15 DM:

Phase type: Single / Three-phase

Maximum singlephase power: 4.6 KVA / 3.68 KW Continuous singlephase power: 4.2 KVA / 3.36 KW Maximum threephase power: 14 KVA / 11.2 KW

Threephase Continuous Power: 12.75 KVA / 10.2 KW

Fuel: Diesel

Voltage: 230 - 400 V Frequency: 50 Hz

Engine: Yanmar 3TNV88 Number of cylinders: 3 Displacement: 1642 cc Engine rpm: 1500 rpm

Emissions standard: StageV

Consumption: 2.7 I / h at 75% of the load

Acoustic Pressure: 62 dBA @ 7 m

Voltage regulator: AVR

Length: 1440 mm Width: 650 mm Height: 810 mm Weight: 485 Kg

Are you looking for a product with different technical characteristics? HERE you can find the area dedicated to MASE vehicle generators or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 3.68
Continuous power single phase (KW): 3.3
Maximum power single phase (KVA): 4.6
Continuous power single phase (KVA): 4.2
Maximum power three phase (KW): 11.2
Continuous power three phase (KW): 10.16
Maximum power three phase (KVA): 14
Continuous power three phase (KVA): 12.7

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Engine: Yanmar 3TNV88, 4 stroke naturally aspirated





Emissions Regulations: Stage 5

Engine rpm (rpm): 1500 Starting system: Electric Engine capacity (cm³): 1642

Number cylinders: 3 Oil capacity (L): 4.8 Cooling: Water

Alternator: Sincrono, autoeccitato, autoregolato, senza spazzole

Poles: 4

Consumption (L/h): 2.7 at 75% of the load

Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 1440 Width (mm): 650 Height (mm): 810 Dry weight (Kg): 485

Silenced: Yes

Super silenced: Yes Voltage regulator: AVR

Engine manufacturer: Yanmar