



TECNOGEN H 13000 TELX GENERATOR SINGLE-PHASE / THREE-PHASE POWER 12 KVA

Product description:

TECNOGEN H13000TELX SINGLE-PHASE / THREE-PHASE POWER GENERATOR 12 KVA

TECNOGEN H13000TELX three-phase generating set of 9,6 KW and single-phase of 3 KW with Honda engine of 3000 rpm powered by gasoline. The TECNOGEN H13000TELX generating set is easy to use and is of small dimensions, manageable and easy to maintain.

The TECNOGEN H13000TELX generating set is equipped with electric start. This genset is perfect both for hobby and professional use, thanks to the reliable Honda gasoline engine and to all the high quality components of which it is composed.

The TECNOGEN H13000TELX group is also used to supply electric current in construction sites and for hobby use. The professional generators are light machines, easy to transport, compact and robust, simple to use and with low operating costs. They also present an excellent quality/price ratio.

On the TECNOGEN H13000TELX generator set it is possible to install lifting hooks, very useful to move the generator with an overhead crane or a small crane.

TECHNICAL CHARACTERISTICS TECNOGEN H13000TELX

Phase type: Singlephase / Threephase

Maximum singlephase power: 4 KVA / 3.2 KW

Continuous use singlephase power: 3.7 KVA / 3 KW

Maximum threephase power: 12 KVA / 9.6 KW Continuous threephase power: 10.9 KVA / 8.7 KW

Voltage: 230 / 400V Frequency: 50Hz



Engine: HONDA GX630

Fuel: Petrol

Starting: Electric / Automatic

Socket panel: 1 x 32A 400V / 1 x 16A 230V

Emissions regulations: Not emitted

Tank capacity: 20 I

Consumption: 4 Lt / h at 75% of the load Autonomy: 5 hours at 75% of the load

Length: 990mm Width: 550 mm Height: 670 mm Weight: 123 Kg

Are you looking for a product with different technical characteristics? HERE you can find the area dedicated to TECNOGEN generating sets or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase / Three phase Maximum power single phase (KW): 3 Maximum power single phase (KVA): 3.8 Maximum power three phase (KW): 9.6 Maximum power three phase (KVA): 12

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: HONDA GC160 Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 688

Number cylinders: 2

Cooling: Air

Fuel tank capacity (L): 20 Consumption (L/h): 4 Running time (h): 5

Acoustic power: 98 dB(A)

Length (mm): 990 Width (mm): 550 Height (mm): 670 Dry weight (Kg): 123

Silenced: No



Super silenced: No ATS Switch device : Optional Voltage regulator: No Engine manufacturer: Honda

