



PRAMAC TG12/3 IP23

Product price:

1.450,00 € tax excluded

Product description:

PRAMAC TG12/3 IP23 PTO Generator Single Phase/Three Phase 12 KVA

PRAMAC TG12/3 IP23 PTO Generator Single Phase 6 KVA and Three Phase 12 KVA with 3000 rpm tractor attachment. The PRAMAC TG12/3 IP23 PTO Generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG12/3 IP23 PTO Generator has a **compound** voltage regulator. The compound regulator allows to stabilize the voltage and avoid damage to the connected devices. The TG12/3 IP23 cardan shaft generator is **very reliable** as it has been built and designed using top quality materials.

A cardan shaft generator that is easy to transport, install and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG12/3 IP23 cardan shaft generator has a required tractor power of 22 KW / 30 HP and a PTO speed of 435 rpm.

Technical characteristics of the PRAMAC TG12/3 IP23 cardan shaft generator Single-phase/Three-phase:

Continuous use power Single-phase: 6 KW

Continuous use power Three-phase: 9.6 KW

Voltage: 230 V / 400 V

Frequency: 50 Hz

PTO speed: 435 rpm

Required tractor power: 22 KW / 30 HP

Length: 746 mm

Width: 580 mm

Height: 958 mm

Weight: 110 Kg

Compound

Sockets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 16A IP44





N.1 3P+N+T CEE 400V 16A IP44

The PRAMAC TG12/3 IP23 cardan shaft generator is a professional tractor unit developed by Pramac which makes it one of the best choices compared to its competitors. The PRAMAC TG12/3 IP23 cardan shaft generator has a sturdy structure with a protective tubular frame. The TG12/3 IP23 cardan shaft generator is equipped with magnetothermal protection, differential protection, voltmeter and frequency meter.

If you are looking for a cardan shaft generator such as the PRAMAC TG12/3 IP23 single-phase/three-phase tractor unit then we recommend that you browse our catalogue of cardan shaft generators to find the one that best meets your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 6

Continuous power single phase (KVA): 6

Continuous power three phase (KW): 9.6

Continuous power three phase (KVA): 12

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 3000

PTO speed (round/min): 435

Required tractor power: 22 KW / 30 HP