



PRAMAC TG20/3 IP23

Cardan generator Single-phase-Three-phase 20kVA

Product price:

1,904.56 € tax excluded

Product description:

PRAMAC TG20/3 IP23 PTO Generator Single/Three-Phase 20 KVA

The PRAMAC TG20/3 IP23 PTO generator delivers 10 KVA in single-phase and 20 KVA in three-phase, with a tractor connection at 3000 rpm. The PRAMAC TG20/3 IP23 PTO generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG20/3 IP23 PTO generator is equipped with a compound voltage regulator. The compound regulator stabilizes the voltage and prevents damage to connected devices. The TG20/3 IP23 PTO generator is highly reliable as it is built and designed with high-quality materials.

Easy to transport, install, and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG20/3 IP23 PTO generator requires a tractor power of 37 kW / 50 HP and a PTO speed of 435 rpm.

Technical specifications of the PRAMAC TG20/3 IP23 PTO Generator Single/Three-Phase:

Continuous power single-phase: 10 kVA

Continuous power three-phase: 20 kVA

Voltage: 230 V / 400 V

Frequency: 50 Hz

PTO speed: 435 rpm

Required tractor power: 37 kW / 50 HP

Length: 958 mm

Width: 645 mm

Height: 1003 mm

Weight: 148 kg

Compound

Outlets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 32A IP44



The PRAMAC TG20/3 IP23 PTO generator is a professional tractor-driven unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC TG20/3 IP23 PTO generator features a sturdy structure with a protective tubular frame. This series is the ideal solution for agricultural applications, enabling access to remote areas even under adverse weather conditions.

The PRAMAC TG20/3 IP23 PTO generator is equipped with circuit breaker protection, residual current protection, voltmeter, and frequency meter.

If you are looking for a PTO generator like the PRAMAC TG20/3 IP23 single/three-phase tractor-driven unit, we recommend browsing our catalog of [PTO generators](#) to find the one that best suits your needs.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 8

Continuous power single phase (KVA): 10

Continuous power three phase (KW): 16

Continuous power three phase (KVA): 20

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 3000

PTO speed (round/min): 435

Required tractor power: 37 KW / 50 HP

