



Shop name



PRAMAC TG30/15 IP23 Cardan generator Single- phase-Three-phase 30KVA AVR

Product price:

2,979.10 € tax excluded

Product description:

PRAMAC TG30/15 IP23 Cardan Generator Single/Three-Phase 30 kVA AVR

PRAMAC TG30/15 IP23 cardan generator, 12 kVA single-phase and 30 kVA three-phase, with tractor connection at 1500 rpm. The PRAMAC TG30/15 IP23 cardan generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG30/15 IP23 cardan generator has an AVR voltage regulator. The AVR regulator stabilizes the voltage and prevents damage to connected devices. The TG30/15 IP23 AVR cardan generator is highly reliable as it has been built and designed using high-quality materials.

Easy to transport, install, and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG30/15 IP23 cardan generator requires a tractor power of 51 kW / 70 HP and a cardan shaft speed of 430 rpm.

Technical specifications of the PRAMAC TG30/15 IP23 AVR Cardan Generator Single/Three-Phase:

Continuous power single-phase: 12 kW

Continuous power three-phase: 24 kW

Voltage: 230 V / 400 V

Frequency: 50 Hz

Cardan shaft speed: 430 rpm



Required tractor power: 51 kW / 70 HP

Length: 958 mm

Width: 645 mm

Height: 1003 mm

Weight: 213 kg

AVR

Sockets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 63A

The PRAMAC TG30/15 IP23 cardan generator is a professional tractor-driven unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC TG30/15 IP23 cardan generator features a robust structure with a protective tubular frame. This series is the ideal solution for agricultural applications, also allowing access to hard-to-reach areas even under adverse weather conditions.

The TG30/15 IP23 cardan generator is equipped with thermal-magnetic protection, residual current protection, voltmeter, and frequency meter.

If you are looking for a cardan generator like the PRAMAC TG30/15 IP23 AVR single/three-phase tractor-driven unit, we recommend browsing our [catalog of cardan generators](#) to find the one that best suits your needs.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 9.6

Continuous power single phase (KVA): 12

Continuous power three phase (KW): 24



Continuous power three phase (KVA): 30

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 1500

PTO speed (round/min): 430

Required tractor power: 51 KW / 70 HP