



PRAMAC TG30/15 IP23

Product price:

2.650,00 € tax excluded

Product description:

PRAMAC TG30/15 IP23 PTO Generator Single Phase/Three Phase 30 KVA AVR

PRAMAC TG30/15 IP23 PTO Generator Single Phase 12 KVA and Three Phase 30 KVA with 1500 rpm tractor attachment. The PRAMAC TG30/15 IP23 PTO Generator has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC TG30/15 IP23 PTO Generator has an AVR voltage regulator. The AVR regulator allows you to stabilize the voltage and avoid damage to the connected devices. The TG30/15 IP23 AVR cardan generator is very reliable as it has been built and designed using top quality materials.

Cardan generator easy to transport, install and position thanks to its compact size, this model is ideal for mounting on a tractor unit. The PRAMAC TG30/15 IP23 cardan shaft generator has a required tractor power of 51 KW / 70 HP and a PTO speed of 430 rpm.

Technical characteristics of the PRAMAC TG30/15 IP23 AVR Single-phase/Three-phase cardan shaft generator:

Continuous use power Single-phase: 12 KW

Continuous use power Three-phase: 24 KW

Voltage: 230 V / 400 V

Frequency: 50 Hz

PTO speed: 430 rpm

Tractor power required: 51 KW / 70 HP





Length: 958 mm

Width: 645 mm

Height: 1003 mm

Weight: 213 Kg

AVR

Sockets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 63A

The PRAMAC TG30/15 IP23 cardan shaft generator is a professional tractor unit developed by Pramac which makes it one of the best choices compared to its competitors. The PRAMAC TG30/15 IP23 cardan shaft generator has a sturdy structure with a protective tubular frame. This series is the ideal solution for agricultural applications that also allows you to reach inaccessible areas even with adverse weather conditions.

The TG30/15 IP23 PTO generator is equipped with magnetothermal protection, differential protection, voltmeter and frequency meter.

If you are looking for a PTO generator such as the PRAMAC TG30/15 IP23 AVR single-phase/three-phase tractor unit then we recommend you browse our catalogue of PTO generators to find the one that best suits your needs.

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Single phase / Three phase





Continuous power single phase (KW): 12

Continuous power single phase (KVA): 12

Continuous power three phase (KW): 24

Continuous power three phase (KVA): 30

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 1500

PTO speed (round/min): 430

Required tractor power: 51 KW / 70 HP