



# PRAMAC TG42/15 IP23

Product price:

**4.500,00 € tax excluded**



## Product description:

PRAMAC PTO Generator TG42/15 IP23 Single-phase/Three-phase 42 KVA AVR

PRAMAC PTO generator TG42/15 IP23 single-phase with 14.7 KVA and three-phase with 42 KVA with 1500 rpm tractor connection. The PRAMAC PTO generator TG42/15 IP23 has a voltage of 230 V / 400 V and a frequency of 50 Hz. The alternator of the PRAMAC PTO generator TG42/15 IP23 has an **AVR** voltage regulator. The TG42/15 IP23 AVR PTO generator is **very reliable** as it has been built and designed using high-quality materials.

Easy to transport, install and position thanks to its compact size, this PTO generator model is ideal for mounting on a tractor unit. The PRAMAC PTO generator TG42/15 IP23 has a required tractor power of 74 KW / 100 HP and a PTO speed of 395 rpm.

## Technical characteristics of the PRAMAC PTO generator TG42/15 IP23 AVR Single-phase/Three-phase:

Continuous single-phase power: 14.7 KW

Continuous three-phase power: 33.6 KW

Voltage: 230 V / 400 V

Frequency: 50 Hz

PTO speed: 395 rpm

Tractor power required: 74 KW / 100 HP

Length: 1110 mm

Width: 720 mm

Height: 1322 mm

Weight: 355 Kg

AVR

## Outlets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 32A IP44

N.1 3P+N+T CEE 400V 63A





The PRAMAC PTO generator TG42/15 IP23 is a professional tractor unit developed by Pramac, making it one of the best choices compared to its competitors. The PRAMAC PTO generator TG42/15 IP23 has a robust structure with a protective tubular frame.

The TG42/15 IP23 PTO generator is equipped with magnetothermal protection, differential protection, voltmeter and frequency meter.

If you are looking for a PTO generator like the PRAMAC TG42/15 IP23 AVR single-phase/three-phase tractor unit, then we recommend browsing our catalog of PTO generators to find the one that best suits your needs.

Images and technical data are not binding. Always refer to the technical data sheet issued by the manufacturer. Manel service does not assume responsibility for any changes made by the manufacturer.

#### **Product features:**

Phase: Single phase / Three phase

Continuous power single phase (KW): 14.7

Continuous power single phase (KVA): 14.7

Continuous power three phase (KW): 33.6

Continuous power three phase (KVA): 42

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 63A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine rpm (rpm): 1500

PTO speed (round/min): 395

Required tractor power: 74 KW / 100 HP