



# HONDA ECT 7000 Petrol Single / Three Phase Generator max. 7 kW

## Product description:

When it comes to a generator on a construction site, you don't want to cut corners on quality. Always choose a Honda for those jobs that need to be done with minimum fuss. They're tough and always ready to go.

## Plenty of energy

Simplicity and cost effectiveness go hand in hand with a condenser/inductive type EC generator. The power produced is perfect for resistive loads like power drills, circular saws and concrete breakers.

## LET'S START WORK

Just fire it up and forget it.

Quick and easy: the accessible ergonomic fuel filler cap is right where you need it – on top. Practical sockets and controls make starting and running the generator quick and simple. Just start it and let it get on with the job, because the unique Oil Alert™ will automatically switch off the ignition if the oil drops below a safe level. It's as safe as safe can be.

## Smooth running

Honda has built an engine mount system into the durable steel frame. These rubber shock absorbers are positioned either side of the engine at 45° and significantly reduce the engine vibration of an already quiet machine.

The photoes are for illustrative purpose only.





---

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 4  
Continuous power single phase (KW): 3.6  
Maximum power single phase (KVA): 5  
Continuous power single phase (KVA): 4.2  
Maximum power three phase (KW): 7  
Continuous power three phase (KW): 6.5  
Maximum power three phase (KVA): 8.75  
Continuous power three phase (KVA): 8.12  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V CEE - 2 x 230V SCHUKO  
Engine: Honda GX390 T1, 4 stroke, OHV  
Engine rpm (rpm): 3000  
Ignition: Transistorized  
Starting system: Manual  
Engine capacity (cm<sup>3</sup>): 389  
Number cylinders: 1  
Oil capacity (L): 1.1  
Cooling: Air  
Alternator: Tripolar  
Bore x stroke (mm): 88 x 64  
Fuel tank capacity (L): 6.2  
Consumption (L/h): 2.75  
Running time (h): 2.25  
Acoustic power: 97 dB(A)  
Acoustic pressure: 86 dB(A)  
Length (mm): 800  
Width (mm): 550  
Height (mm): 540  
Dry weight (Kg): 77  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: Compound  
Engine manufacturer: Honda  
Video: V0JyzKGrpJE

