



# TECNOGEN LW22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

## Product description:

### TECNOGEN LW22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Electric start diesel generators, water-cooled, 3000 rpm, available in both single-phase and three-phase versions, with powers from 11.7 to 34.7 kVA MAX. Sturdy and reliable, they are suitable to operate for long periods despite the high rotation rate. The set-up relative to the base-mounted versions includes a built-in fuel tank with a capacity of 52 l, a metal grille placed to protect the radiator and a professional electrical panel, entirely made of ABS with a high degree of protection, equipped with instruments that respect the strictest safety standards. The silenced models are also equipped with a soundproofed canopy in hot-dip galvanized steel. The generators of the W 3000 series are the ideal choice for applications with automatic intervention panel or for use in the mechanical / industrial field.

The image is purely indicative.

## Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 6.2  
Maximum power single phase (KVA): 7.8  
Maximum power three phase (KW): 18.7  
Maximum power three phase (KVA): 23.4  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400



---

Engine: HONDA GC160

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 1372

Number cylinders: 4

Cooling: Water

Fuel tank capacity (L): 54

Consumption (L/h): 4.7

Running time (h): 11.4

Acoustic power: 94 dB(A)

Length (mm): 1750

Width (mm): 770

Height (mm): 1070

Dry weight (Kg): 460

Silenced: No

Super silenced: Yes

ATS Switch device : Yes

Voltage regulator: Compound / AVR (optional)

Engine manufacturer: Lombardini

