



TECNOGEN LW22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Product price:

7,700.00 € tax excluded

Product description:

TECNOGEN LW22000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Electric start diesel generators, water-cooled, 3000 rpm, available in both single-phase and three-phase versions, with powers from 11.7 to 34.7 kVA MAX. Sturdy and reliable, they are suitable to operate for long periods despite the high rotation rate. The set-up relative to the base-mounted versions includes a built-in fuel tank with a capacity of 52 l, a metal grille placed to protect the radiator and a professional electrical panel, entirely made of ABS with a high degree of protection, equipped with instruments that respect the strictest safety standards. The silenced models are also equipped with a soundproofed canopy in hot-dip galvanized steel. The generators of the W 3000 series are the ideal choice for applications with automatic intervention panel or for use in the mechanical / industrial field.

The image is purely indicative.

Product features:

Phase: Single phase / Three phase Maximum power single phase (KW): 6.2 Maximum power single phase (KVA): 7.8 Maximum power three phase (KW): 18.7 Maximum power three phase (KVA): 23.4

Fuel: Diesel

Frequency (Hz): 50



Voltage (V): 230 / 400 Engine: HONDA GC160 Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 1372

Number cylinders: 4 Cooling: Water

Fuel tank capacity (L): 54 Consumption (L/h): 4.7 Running time (h): 11.4 Acoustic power: 94 dB(A)

Length (mm): 1750 Width (mm): 770 Height (mm): 1070 Dry weight (Kg): 460

Silenced: No

Super silenced: Yes ATS Switch device: Yes

Voltage regulator: Compound / AVR (optional)

Engine manufacturer: Lombardini