



HONDA Outboard BF 15 LHU 56 cm Shaft With Tiller 11.2 kW 15 Hp 350 cm³

Product price:

2.575,09 € tax excluded

Product description:

HONDA BF15DK2 LHU outboard shaft 56cm

HONDA BF15DK2 LHU outboard engine 15 or 20 horsepower incredibly practical and portable, with well-placed retractable handles. They are perfect for any boat that needs power in a small size.

These 350 cm³ 4-stroke Honda engines are easy to start, thanks to the decompression system and PGM-IG programmed ignition. The ignition system precisely delivers the right amount of air/fuel mixture to the twin cylinders. Even when cold, the engine is able to deliver all the power required.

HONDA BF15DK2 LHU have an automatic decompression system that makes starting easier. During forward travel, the propeller is driven normally through the water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference. This unique reverse exhaust system directs bubbles out of the propeller so it can "grip" the water. The result is immediate response and very precise control.

The lightweight HONDA BF15DK2 LHU outboard rises easily in five steps. Both the manual start and electric start versions allow for raising and lowering, allowing you to adjust the boat's trim for maximum performance and fuel efficiency at all times. This also prevents damage to the propeller blades when the boat is close to rocks or shallow waters.

HONDA BF15DK2 LHU engines have a reverse lever that allows you to shift gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. Plus, the soft-grip, twist-lock throttle knob minimizes operating effort, increasing handling. You can throttle up and slow down as needed to navigate, or keep the control locked as cruise control.

HONDA BF15DK2 LHU outboards are available with rudder and remote control options. The





remote control option displays engine warning lights, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing on other activities. It's unlikely, but if there's a problem, you'll have time to act.

First, the aluminum housing is anodized using Honda's patented "double seal" process. Then a layer of epoxy primer is applied before the silver gloss paint. As additional UV protection, a clear resin is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

TECHNICAL CHARACTERISTICS HONDA BF15DK2 LHU

Net Power (kW): 11.2
Net Power (Hp): 15
Displacement: 350 cm³
Shaft length: Long
Dry weight (Kg): 49.5
Starter: Electric / Manual
Ignition system: Electronic PGM-IG
Control type: Bar
Setup and engine lifting: Manual / Manual 5 positions
Transom height (mm): 563
Length (mm): 650
Width (mm): 350
Height (mm): 1240
Bore x stroke: 59 x 64 mm
Engine Brand: Honda
Engine Type: OHV, 4 stroke
Number of cylinders: 2
Speed at full throttle (rpm): 4500-5500
Cooling system: Water
Battery charge capacity (A): 6

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.

Product features:

Fuel: Gasoline
Engine: OHV, 4 stroke
Ignition: Electronic PGM-IG
Starting system: Electric and recoil





Number cylinders: 2
Cooling: Water (with thermostat)
Reduction ratio: 2.08
Rpm at full throttle (rpm): 4500 - 5500
Appearance and engine lifting: Manual / Manual 5 position
Transom height (mm): 563
Fuel tank capacity (L): 12
Length (mm): 650
Height (mm): 1240
Dry weight (Kg): 49.5
Shaft Length: L
Controls: Tiller