



# HONDA Outboard BF 15 LHSU Long Shaft With Tiller 11.2 kW 350 cm<sup>3</sup>

**Product price:** 

2,940.00 € tax excluded

### **Product description:**

#### HONDA OUTBOARD BF15DK2 LHSU 56CM SHAFT

HONDA BF15DK2 LHSU outboard engine 15 or 20 horsepower incredibly practical and portable, with well placed retractable handles. They are perfect for any boat that needs power in a small size.

These 350 cm<sup>3</sup> 4-stroke Honda engines are easy to start, thanks to the decompression system and PGM-IG programmed ignition. The ignition system precisely delivers the right amount of air/fuel mixture to the twin cylinders. Even when cold, the engine is able to deliver all the power required.

HONDA BF15DK2 LHSU have an automatic decompression system that makes starting easier. During forward travel, the propeller is driven normally through the water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference.

The lightweight HONDA BF15DK2 LHSU outboard rises easily in five steps. Both the manual start and electric start versions allow for raising and lowering, allowing you to adjust the boat's trim for maximum performance and fuel efficiency at all times. This also prevents damage to the propeller blades when the boat is close to rocks or shallow waters.



HONDA BF15DK2 LHSU engines have a reverse lever that allows you to shift gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. Plus, the soft-grip, twist-lock throttle knob minimizes operating effort, increasing handling.

HONDA BF15DK2 LHSU foulboats are available with rudder and remote control options. The remote control option displays engine warning lights, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing on other activities. It's unlikely, but if there's a problem, you'll have time to take action.

## TECHNICAL CHARACTERISTICS HONDA BF15DK2 LHSU

Net Power (kW): 11.2 Net Power (Hp): 15 Displacement: 350 cm<sup>3</sup> Shaft length: Long Dry weight (Kg): 52

Starter: Electric / Manual

Ignition system: Electronic PGM-IG

Control type: Bar

Setup and engine lifting:Manual / Manual 5 positions

Transom height (mm): 563

Length (mm): 650 Width (mm): 350 Height (mm): 1240

Bore x stroke: 59 x 64 mm Engine Brand: Honda

Engine Type: OHV, 4 stroke

Number of cylinders: 2

Speed at full throttle (rpm): 4500-5500

Cooling system: Water

Battery charging capacity (A): 12

Are you looking for an outboard with different technical characteristics? <u>Here</u> you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.

#### **Product features:**

Fuel: Gasoline

Engine: OHV, 4 stroke Ignition: Electronic PGM-IG



Starting system: Electric and recoil

Engine capacity (cm³): 350

Number cylinders: 2

Cooling: Water (with thermostat)

Bore x stroke (mm): Reduction ratio: 2.08

Rpm at full throttle (rpm): 4500 - 5500

Appearance and engine lifting: Manual / Manual 5 position

Transom height (mm): 563

Net power (kW):

Fuel tank capacity (L): 12

Length (mm): 650

Width (mm): Height (mm):

Dry weight (Kg): 52 Shaft Length: L Controls: Tiller

