



PRAMAC E4500 SINGLE PHASE

Product price:

1.185,00 € tax excluded

Product description:

PRAMAC E4500 Single-phase Generator 3.5 KW

PRAMAC E4500 single-phase generator with 3.5 KW power and Yanmar engine at 3000 rpm in an open version. The PRAMAC E4500 generator is equipped with a manual recoil start with auto-rewind. The alternator of the PRAMAC E4500 generator is brushless with a capacitor voltage regulator. The Yanmar engine makes this generator **very reliable**, and its design uses high-quality materials.

Thanks to its very low weight and **compact dimensions**, it is convenient to transport wherever you need it most. The PRAMAC E4500 generator is suitable for outdoor use on small construction sites or for small outdoor hobby work.

Technical characteristics of the PRAMAC E4500 generator:

Maximum single-phase power: 3.5 KW

Continuous single-phase power: 3 KW

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Engine: Yanmar L70N Recoil

Starting: Recoil start

Consumption: 1.2 Lt/h at 100% load

Length: 760 mm

Width: 540 mm

Height: 560 mm

Weight: 54 Kg





CONTROL PANEL

Controls:

- Start - Stop control lever
- Decompression lever
- Ignition: Recoil auto-rewind
- Fuel tap

Outlets:

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 16A IP44

The PRAMAC E4500 current generator is a diesel generator developed by Pramac to ensure a high level of quality and performance at an attractive price. The PRAMAC E4500 current generator is ideal for intensive applications, characterized by a robust structure with a supporting tubular frame that simplifies both its use and maintenance operations.

The E4500 current generator is the essential tool to meet professional applications.

If you are looking for a generator like the PRAMAC E4500 current generator, then we recommend browsing our catalog of land generators to find the one that best suits your needs.

Images and technical data are not binding. Always refer to the technical data sheet issued by the manufacturer. Manel service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.5

Continuous power single phase (KW): 3

Maximum power single phase (KVA): 3.9

Continuous power single phase (KVA): 3.3

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A SCHUKO IP54 - 1 x 230V 16A 2P+T CEE IP44

Engine: Yanmar L70N Recoil, naturally aspirated

Engine rpm (rpm): 3000





Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter

Engine capacity (cm³): 320

Oil capacity (L): 1.1

Cooling: Air

Alternator: Brushless

Poles: 2

Fuel tank capacity (L): 3.5

Consumption (L/h): 0.9 at 75% of the load / 1.2 at 100% of the load

Running time (h): 3.8 at 75% of the load / 2.8 at 100% of the load

Length (mm): 760

Width (mm): 540

Height (mm): 560

Dry weight (Kg): 54

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Capacitor

Engine manufacturer: Yanmar