



PRAMAC E4500 THREE PHASE

Product price:

1.525,00 € tax excluded

Product description:

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.48

Continuous power single phase (KW): 1.84

Maximum power single phase (KVA): 3.1

Continuous power single phase (KVA): 2.3

Maximum power three phase (KW): 3.7

Continuous power three phase (KW): 3.2

Maximum power three phase (KVA): 4.7

Continuous power three phase (KVA): 4

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 230V 16A IP54 SCHUKO - 1 x 230V 16A IP44 2P+T CEE

Engine: Yanmar L70N Recoil, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter

Engine capacity (cm³): 320

Oil capacity (L): 1.1

Cooling: Air

Alternator: With brushes

Poles: 2

Fuel tank capacity (L): 3.5

Consumption (L/h): 0.9 at 75% of the load / 1.2 at 100% of the load





Running time (h): 3.8 at 75% of the load / 2.8 at 100% of the load

Length (mm): 760

Width (mm): 540

Height (mm): 560

Dry weight (Kg): 70

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar

