



PRAMAC E6500 SINGLE PHASE

Product price:

1,853.10 € tax excluded

Product description:

PRAMAC E6500 Single-phase 5.3 KW generator set

PRAMAC E6500 single-phase 5.3 KW generator set with Yanmar diesel engine at 3000 rpm in open version. The PRAMAC E6500 generator set is equipped with manual recoil starter with self-winding mechanism. The PRAMAC E6500 generator set alternator is brushless with capacitor voltage regulator. The Yanmar engine makes this generator set **very reliable** and its design is made with high quality materials.

Thanks to its very low weight and its **compact dimensions** it is easy to transport where you need it most. The PRAMAC E6500 generator is suitable for outdoor use on small construction sites or for small outdoor jobs for hobby use.

Technical characteristics of the PRAMAC E6500 generator:

Maximum power Single phase: 3.5 KW

Continuous use power Single phase: 3 KW

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Engine: Yanmar L70N Recoil

Starting: Recoil

Consumption: 1.2 Lt/h at 100% load

Length: 760 mm

Width: 540 mm

Height: 560 mm

Weight: 54 Kg

CONTROL PANEL

Controls:

- Start - Stop control lever
- Decompression lever
- Ignition: Self-winding
- Fuel tap

**Sockets:**

N.1 SCHUKO 230V 16A IP54

N.1 2P+T CEE 230V 32A IP44

The PRAMAC E6500 generator is a diesel generator developed by Pramac to guarantee a high level of quality and performance at an attractive price. The PRAMAC E6500 generator is ideal for intensive applications, characterized by a robust structure with a load-bearing tubular frame that simplifies both its use and maintenance operations.

The E6500 generator is the essential tool to satisfy professional applications.

If you are looking for a generator set like the PRAMAC E6500 generator then we recommend you browse our catalog of [terrestrial generator sets](#) to find the one that best meets your needs.

Images and technical data are not binding. Please always consult the technical data sheet released by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 5.3

Continuous power single phase (KW): 4.4

Maximum power single phase (KVA): 5.9

Continuous power single phase (KVA): 4.9

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A SCHUKO IP54 - 1 x 230V 32A 2P+T CEE IP44

Engine: Yanmar L100N, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter

Engine capacity (cm³): 435

Oil capacity (L): 1.6

Cooling: Air

Poles: 2

Fuel tank capacity (L): 5.5

Consumption (L/h): 1.45 at 75% of the load / 1.9 at 100% of the load

Running time (h): 3.8 at 75% of the load / 2.8 at 100% of the load

Length (mm): 760

Width (mm): 540



Shop name

Height (mm): 560
Dry weight (Kg): 94
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Capacitor
Engine manufacturer: Yanmar



PrestaShop