



PRAMAC GBW10Y STAGE V APERTO CON QUADRO COMANDO AUTOMATICO

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 7.47

Continuous power three phase (KW): 6.81

Maximum power three phase (KVA): 9.34

Continuous power three phase (KVA): 8.51

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1116

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 3.5

Cooling: Water

Alternator: Linz E1S13SB , with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2 at 75% of the load / 2.6 at 100% of the load

Running time (h): 25.6 at 75% of the load / 19.2 at 100% of the load

Length (mm): 1600

Width (mm): 870



Shop name

Height (mm): 875

Dry weight (Kg): 250

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Compound

Engine manufacturer: Yanmar



PrestaShop