



# PRAMAC GBW22Y APERTO CON QUADRO COMANDO MANUALE

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 15.48

Continuous power three phase (KW): 14.1

Maximum power three phase (KVA): 19.35

Continuous power three phase (KVA): 17.63

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 2190

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 7.4

Cooling: Water

Alternator: Linz E1S13MF, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 3.8 at 75% of the load / 5 at 100% of the load

Running time (h): 13.4 at 75% of the load / 10.1 at 100% of the load

Length (mm): 1600

Width (mm): 870



Height (mm): 1000

Dry weight (Kg): 507

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar