



PRAMAC GBW35Y APERTO CON QUADRO COMANDO MANUALE (MCP)

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 29.87

Continuous power three phase (KW): 28.38

Maximum power three phase (KVA): 37.34

Continuous power three phase (KVA): 35.48

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 4TNV98-IGPGE, naturally aspirated

Emissions Regulations: Stage 3A

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3319

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10.5

Cooling: Water

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 5.8 at 75% of the load / 7.7 at 100% of the load

Running time (h): 8.8 at 75% of the load / 6.6 at 100% of the load



Length (mm): 2000

Width (mm): 920

Height (mm): 1100

Dry weight (Kg): 558

Inverter: No

AVR: Yes

Compound: No

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Yanmar

