



# PRAMAC GSL30D APERTO CON QUADRO COMANDO MANUALE (MCP)

## Product description:

### Product features:

Phase: Three phase

Maximum power three phase (KW): 25.55

Continuous power three phase (KW): 24.31

Maximum power three phase (KVA): 31.94

Continuous power three phase (KVA): 30.39

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Deutz AG F4L2011, naturally aspirated

Emissions Regulations: Stationary Use

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Air

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 91

Consumption (L/h): 5.7 at 75% of the load / 7.5 at 100% of the load

Running time (h): 15.9 at 75% of the load / 12.1 at 100% of the load

Length (mm): 1400

Width (mm): 750





---

Height (mm): 1700  
Dry weight (Kg): 663  
Inverter: No  
AVR: Yes  
Compound: No  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Deutz